

Save energy, improve privacy and aesthetics on budget with 3M[™] Sun Control Window Film Silver P18 Series.

- Classic silver reflective film with excellent solar protection
- Great heat rejection helps provide energy savings and improved comfort
- ► Helps reduce glare and eye discomfort
- Increased reflection helps enhance daytime privacy
- Can create a more uniform exterior appearance
- Comprehensive warranty from 3M

| Energy Savings | **** | | | | |
|----------------------------|------|--|--|--|--|
| Glare Rejection | **** | | | | |
| Visible Reflection | ** | | | | |
| Visible Light Transmission | ** | | | | |
| Best **** Better *** | | | | | |

Good ★★★ Fair ★★ Not Recommended ★ In comparison to other 3M[™] Sun Control Window Films

Valued Associations and Alliances:













Climate Zone 5

Ford Motor Company Headquarters, Detroit, Michigan 83,000 sq ft installation of Silver P18

Customer Issues:

- Maintaining comfortable temperatures
- Difficulty viewing computer screens due to glare from the sun



Product Performance and Technical Data

| | | Visible Light | | | | Solar | U Value | | | | | |
|--------------------------|------------|-------------------------|-------------------------|-------------|-----------------------------------|---------------------------------------|---------------|-----------|-------------------------|----------------------|--------------------|----------------------------------------------|
| Glass Type (All 1/4") | Film Type | Reflected (Interior) | Reflected (Exterior) | Transmitted | Total Solar Energy Rejected | Heat Gain Coefficient (G Value) | btu/ hft²F | w/ m²K | Solar Heat Reduction | UV Light Rejected | Glare Reduction | Visible Light to Solar Heat Gain Ratio |
| Clear | Silver P18 | 58% | 56% | 17% | 77% | 0.23 | 0.93 | 5.3 | 72% | 99% | 81% | 0.7 |
| Tinted | Silver P18 | 58% | 23% | 10% | 74% | 0.27 | 0.93 | 5.3 | 58% | 99% | 82% | 0.4 |
| Double Clear | Silver P18 | 58% | 55% | 15% | 67% | 0.33 | 0.45 | 2.6 | 53% | 99% | 80% | 0.5 |
| Double Tinted | Silver P18 | 58% | 23% | 9% | 73% | 0.27 | 0.45 | 2.6 | 47% | 99% | 81% | 0.3 |

| LEED Certification Window films may be used toward the following LEED credits | | | | | | | | | |
|----------------------------------------------------------------------------------|--------------|----------|--------------|--------|--------------|----------|------|--|--|
| ► SS-8 | ► MR 1.1-1.2 | ► EQ-7.1 | ► EQ-8.1-8.2 | ► EA-1 | ► MR 5.1-5.2 | ► EQ-7.2 | ► ID | | |

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

3M Renewable Energy Division 3M Center, Building 235-2S-27 St. Paul, MN 55144-1000 3M.com/windowfilm

3M is a trademark of 3M. Used under license in Canada. Please recycle. Printed in the U.S.A. © 3M 2016. All rights reserved. 98-0150-0754-9